

Załącznik 2

BREATHER VALVE 1000 SERIE
+F.A. integrated Tornado Type



SIZE	SET Pressure [mbar]	SET Vacuum [mbar]
DN [mm]	32	2,2
	50	

VACUUM

FLOW RATE PRESSURE
[Nm³/h] [mbar]

0	-2,2
34,07	-2,27
48,59	-2,35
60,01	-2,43
69,87	-2,51
78,78	-2,59
87,04	-2,68
94,82	-2,77
102,24	-2,86
109,39	-2,96
116,31	-3,06
123,06	-3,16
129,66	-3,27
136,15	-3,38
142,55	-3,49
148,87	-3,61
155,13	-3,73
161,35	-3,86
167,54	-3,99
173,70	-4,12
179,85	-4,26
185,99	-4,40

PRESSURE

FLOW RATE PRESSURE
[Nm³/h] [mbar]

0	32
183,77	33,07
262,06	34,18
323,65	35,33
376,87	36,52
424,93	37,74
469,47	39,01
511,43	40,32
551,46	41,67
589,99	43,07
627,33	44,51
663,71	46,01
699,33	47,55
734,34	49,15
768,84	50,80
802,95	52,50
836,74	54,26
870,28	56,08
903,65	57,97
936,88	59,91
970,04	61,92
1003,16	64,00

